专业 · 创新 · 品质 · 服务

website:
https://www.oil-pressing-machine.com

榨油机精炼设备领先品牌

服务热线:+86 19906365856
电　话: 0536-3522939
传　真: 0536-3522939
邮　箱: Gavin@oil-pressing-machine.com

WeChat&WhatsApp

If not get any response from the email:Gavin@oil-pressing-machine.com
please contact Email: Roryshanshan@gmail.com

钱隆

盛世赫程机械有限公司
SHENG SHI HE CHENG JI XIE YOU XIAN GONG SI

山东盛世赫程机械有限公司

山东盛世赫程机械有限公司

山东盛世赫程机械有限公司位于历史文化名城九州之一的青州。[illegible]

从2008年开始，研发生产的自动化精滤液压榨油机系列，已有11年的历史。[illegible]

Qingzhou Shengshi He cheng Machinery Factory is located in the famous historical and cultural city in Kyushu, Qingzhou. [illegible]

From the beginning of 2008, automatic precision filtration hydraulic press machine series of R & D and production, has 11 years of history, [illegible]

山东盛世赫程机械有限公司

§ YY-1200型四顶缸超高压大型榨油机

本产品采用德国先进液压系统，动力源系超高压组合液压站，液压站配高低组合双联泵，油缸提升速度成倍提升，工作泵压力最高达63Mpa。四缸最大推力可达1300吨，料筒采用条排式直线缝隙出油面积是打洞料筒出油面积的15倍，出油速度更快，压力高，出油率高2-3%斤。

主要适用于化工原料的压榨，脱水；污水处理厂的污泥脱水，油料预榨、白土压榨、油泥压榨及果蔬的脱水。

This product adopts Germany advanced hydraulic system, power system is ultra high pressure combined hydraulic station, hydraulic station with high and low combination of double pump, cylinder lifting speed doubled, the working pump pressure up to 63Mpa. The maximum thrust of the four cylinder can reach 1300 tons, and the oil discharge area of the straight line slot is 15 times of the oil discharge area of the barrel, and the speed of oil extraction is faster, the pressure is higher and the oil yield is 2-3% kg.

It is mainly applicable to the squeezing and dewatering of chemical raw materials; sludge dewatering in sewage treatment plant, oil pre pressing, clay pressing, sludge pressing and dehydration of fruits and vegetables.

产品规格
Product specifications

产品型号 Product model	工作压力 Working pressure	料筒直径 Cylinder diameter	料筒高度 Cylinder height	配用电源 Power Supply	电机功率 Motor power
1200型四缸超高压大型榨油机	60Mpa	80-120cm（可定做）	100-170cm（可定做）	380V	7.5Kw

§ YY720型双顶缸超高压大型全自动榨油机

本产品采用德国先进液压系统，动力源系超高压组合液压站，液压站配高低组合双联泵，油缸提升速度成倍提升，工作泵压力最高达63Mpa。双缸最大压力可达720吨，料筒采用条排式直线缝隙出油面积是打洞料筒出油面积的15倍，出油速度更快，压力高，出油率高2-3%斤。

主要适用于化工原料的压榨，脱水；污水处理厂的污泥脱水，油料预榨、白土压榨、油泥压榨及果蔬的脱水。

This product adopts Germany advanced hydraulic system, power system is ultra high pressure combined hydraulic station, hydraulic station with high and low combination of double pump, cylinder lifting speed doubled, the working pump pressure up to 63Mpa. The maximum pressure of the double cylinder can reach 720 tons, and the oil discharge area of the straight line slot is 15 times of the oil outlet area of the barrel, the oil outlet speed is faster, the pressure is higher, and the oil yield is 2-3% kg.

It is mainly applicable to the squeezing and dewatering of chemical raw materials; sludge dewatering in sewage treatment plant, oil pre pressing, clay pressing, sludge pressing and dehydration of fruits and vegetables.

产品规格
Product specifications

产品型号 Product model	工作压力 Working pressure	压榨容量 Crushing capacity	榨圈直径 Pressing ring diameter	料筒长度 Material barrel length	配用电源 Power Supply	电机功率 Motor power
（YY720型）双顶缸超高压大型全自动榨油机	60Mpa	约600斤	600mm（可定做）	100cm	380V	7.5Kw

§ YY355CG-A 不锈钢榨油机

本产品采用德国先进液压系统，动力源系超高压组合液压站，液压站配高低组合双联泵，油缸提升速度成倍提升，工作泵压力最高达63Mpa。料筒采用条排式直线缝隙出油面积是打洞料筒出油面积的15倍，出油速度更快，压力高，出油率高2-3%斤。主要适用于茶籽、胡麻籽、核桃仁、杏仁、松子、牡丹籽等高端油料作物的压榨，也可用作各种化工原料及果蔬的脱水。

This product adopts Germany advanced hydraulic system, the power source is ultra high pressure combined hydraulic station Hydraulic station with high and low combination of double pumps, cylinder lifting speed doubled, the work pumpThe pressure is up to 63Mpa.The material cylinder adopts a straight line with slit rows, and the oil outlet area is 15 times of the oil discharge area of the hole barrel,Oil out faster, high pressure oil yield, 2-3% jin.Mainly applies to tea seeds, Hu Mazi, walnut, almonds, pine nuts,peony seeds and other high-endThe pressing of oil crops can also be used as dehydration of various chemical raw materials and fruits and vegetables.

产品规格
Product specifications

产品型号 Product model	工作压力 Working pressure	料筒直径 Cylinder diameter	料筒高度 Cylinder height	配用电源 Power Supply	电机功率 Motor power
（355CG-A）不锈钢榨油机	60Mpa	30-60cm（可定做）	50-80cm（可定做）	380/220V	2.2Kw

§ YY325CG-A型条梯形排式全自动榨油机

本产品采用世界先进液压系统，动力源系超高压组合液压站，[illegible]

This product adopts the world advanced hydraulic system, the power system is ultra high pressure combined hydraulic station, hydraulic station with high and low combination of double pumps, cylinder lifting speed doubled, the working pump pressure up to 63Mpa. The oil drainage area of the straight line slot of the material cylinder is 15 times of the oil output area of the barrel, the oil production rate is faster, the pressure is higher, and the oil yield is 2-3% kg.

It is mainly used in the squeezing of tea seed, rapeseed, peanut, soybean, Hu Mazi, clay, animal oil and so on. It can also be used as dewatering agent for various chemical raw materials and fruits and vegetables.



产品规格
Product specifications

产品型号 Product model	工作压力 Working pressure	料筒直径 Cylinder diameter	料筒高度 Cylinder height	配用电源 Power Supply	电机功率 Motor power
（325CG-A）[illegible]	60Mpa	30-60cm（可定做）	50-80cm（可定做）	380/220V	2.2Kw

§ 300CG-B型梯形条排式全自动榨油机

本产品采用世界先进液压系统，动力源系超高压组合液压站，[illegible]

This product adopts the world advanced hydraulic system, the power system is ultra high pressure combined hydraulic station, hydraulic station with high and low combination of double pumps, cylinder lifting speed doubled, the working pump pressure up to 63Mpa. High capacity, high pressure, high oil yield. It is mainly used in the squeezing of tea seed, rapeseed, Hu Mazi, peanut, soybean, clay, animal oil and so on. It can also be used as dewatering agent for various chemical raw materials and fruits and vegetables.

产品规格
Product specifications

产品型号 Product model	工作压力 Working pressure	料筒直径 Cylinder diameter	料筒高度 Cylinder height	配用电源 Power Supply	电机功率 Motor power
（300CG-B）[illegible]	60Mpa	30-60cm（可定做）	50-80cm（可定做）	380/220V	2.2Kw

§ YY400型盘子式全自动榨油机

本产品采用世界先进液压系统，动力源系超高压组合液压站，[illegible]

This product uses the world advanced hydraulic system the power source is the ultra high pressure hydraulic station, hydraulic station with high Low combination of dual pump, cylinder lifting speed doubled, working pump pressure up to 63Mpa.
Material cylinder using a row of straight line gap out of the oil area is 15 times the size of the hole in the hole, out of oilFaster, high pressure, high oil yield 2-3% kg.Mainly used to crush tea seed, peanut, soybean, Hu Mazi, clay, animal oil, can also be used as Various chemical raw materials and the dehydration of fruits and vegetables.

产品规格
Product specifications

产品型号 Product model	工作压力 Working pressure	料筒直径 Cylinder diameter	料筒高度 Cylinder height	配用电源 Power Supply	电机功率 Motor power
（YY400型）[illegible]	60Mpa	30-60cm（可定做）	50-80cm（可定做）	380/220V	2.2Kw

§ YY355CG-A型梯形条排式全自动榨油机

产品采用德国先进的液压系统，[illegible]

The product uses the hydraulic system of Germany advanced power source system, super high pressure combined Hydraulic pump station, pump pressure can reach 63Mpa. Press pressure high with,High oil yield, compact structure, high efficiency and energy saving, constant temperature control, ring guard Born advantages; the device easy to operate, safe and reliable, and greatly reduce theThe labor intensity of workers. There is a whole solution for flax press Shorten the time of pressing flax, thoroughly, improve the oil yield, the product widely is suitable For flax, soybean, Rapeseed,peanut, sesame, walnut kernel, tea seed, almond,Press the pine nuts and other oil crops.

产品规格
Product specifications

产品型号 Product model	工作压力 Working pressure	料筒直径 Cylinder diameter	料筒高度 Cylinder height	配用电源 Power Supply	电机功率 Motor power
（355CG-A）[illegible]	60Mpa	30-60cm（可定做）	50-80cm（可定做）	380/220V	2.2Kw

§ 250ZY普通自动出饼型榨油机（钻孔式）

增压式榨油机，配用柱塞泵，单料桶，[illegible]

Booster type press machine, equipped with piston pump, single barrel, ring type cake, lifting the press speed, time saving, labor saving. Large capacity, high pressure, high oil rate. Mainly used in peanut, soybean, tea seed, linseed, clay, animal oil press and also can be used for all kinds of chemical raw materials and fruit and vegetable dehydration.

产品规格
Product specifications

产品型号 Product model	工作压力 Working pressure	料桶直径 Cylinder diameter	料桶高度 Cylinder height	配用电源 Power Supply	电机功率 Motor power
（250ZY）型[illegible]	20-40Mpa	30-60cm（可定做）	50-80cm（可定做）	380/220V	2.2Kw

§ 1800型全自动压榨机

本产品设备自动化程度高，易操作，无需人工，[illegible]

The equipment is highly automated, easy to operate, and requires no labor. It can produce 1-10 tons per hour and work thrust up to 1800 tons. The sludge treatment has a moisture content of 40%. The oil residue ratio of oil press can reach 3%-5%.

Mainly used in large refineries, large edible oil plants, starch plants, animal oil plants, slaughterhouse sludge treatment, waste white clay treatment, mining stone plants, mining plants, sand washing sand sand plants, sewage treatment stations, environmental protection, municipal engineering For the power plant, gas coking plant, steel mill, pickling mud, chemical plant, cement plant, food factory, paper mill and other industries and urban sewage channel sludge treatment.

产品规格
Product specifications

产品型号 Product model	工作压力 Working pressure	料桶直径 Cylinder diameter	料桶高度 Cylinder height	配用电源 Power Supply	电机功率 Motor power
（1800）型全自动压榨机	25Mpa	180cm（可定做）	50cm（可定做）	380V	20Kw

§ 废弃油脂专用三相离心机

本产品自动化程度高，[illegible]

The degree of automation of this product is high. The feeding, transporting and discharging of this product are carried out during the operation of the equipment, and continuous feeding is realized. Reduce the labor intensity of workers, and the operation is simple and accurate.

This product adopts the current international advanced technology centripetal pump adjustment, which can be adjusted directly during the operation of the equipment without stopping the machine and opening the cover for easy operation.

Clean and non-polluting, the separation and unloading of feed in the production of this product are carried out in fully enclosed equipment, no gas and dust pollution on the site environment, to ensure the cleanliness of the production environment and the health of workers.

The operation is stable and reliable. This product adopts high performance planetary differential, reliable performance, continuous operation and no fault. It adopts double frequency conversion to start, and can adjust the differential ratio within a certain range to achieve the best separation effect.

产品规格
Product specifications

产品型号 Product model	工作产量 Working output	离心转速 Centrifugal speed	转鼓直径	转鼓长度	配用电源 Power Supply	主驱电机功率
废弃油脂专用三相离心机	1-10吨/h	3000r/min	37-40cm（可定做）	1.8m	380V	[illegible]

§ 全自动四柱自动上料榨油机

可自动压榨、自动卸榨，解决了手动上料的缺点，节省了大量人工成本。[illegible]

It can be automatically pressed and automatically retracted, which solves the shortcomings of manual feeding and saves a lot of labor costs.
[illegible]

产品规格
Product specifications

产品型号 Product model	工作压力 Working pressure	压榨容量 Crushing capacity	榨圈直径	料筒长度	配用电源 Power Supply	电机功率 Motor power
[illegible]	60Mpa	[illegible]	450mm（可定做）	70cm	380V	5.5Kw

§ 300型榨油机流水线

可根据用户要求设计制造生产日产1-100吨流水线榨油机。

超高压快速榨油机生产线，配用齿轮柱塞连体泵，使用预压成型装置，流水线料桶，提圈式出饼，提升压榨速度快，省工、省时、省力。日产量可达10-30吨。

The production line of ultra high pressure quick press machine is equipped with gear plunger connecting pump,The pre pressing forming device, the pipeline barrel and the ring out type cake are used,The utility model has the advantages of fast crushing speed, labor saving, time saving and labor saving. Daily output up to10-30 tons.

产品规格
Product specifications

产品型号 Product model	工作压力 Working pressure	料筒直径 Cylinder diameter	料筒高度 Cylinder height	配用电源 Power Supply	电机功率 Motor power
300型榨油机流水线	≤30Mpa	35-60cm（可定做）	50-90cm（可定做）	380/220V	4Kw

§ 100型条排式螺旋榨油机

产品规格
Product specifications

产品型号：100型条排式螺旋榨油机
电机功率：7.5Kw
生产率：120-200Kg/h
主轴转速：35-40r/min
额定电压：380V
Product model: 100 type screw press
The motor power: 7.5 Kw
Productivity: 120-200 kg/h
The spindle speed: 35-40 r/min
Rated voltage: 380 v

§ 100型圆排式螺旋榨油机

产品规格
Product specifications

产品型号：100型圆排式螺旋榨油机
电机功率：7.5Kw
生产率：120-200Kg/h
主轴转速：35-40r/min
额定电压：380V
Product model: 100 type screw press
The motor power: 7.5 Kw
Productivity: 120-200 kg/h
The spindle speed: 35-40 r/min
Rated voltage: 380 v

§ YY-60型不锈钢气压滤油机

气压式滤油机针对小型榨油厂等用户，适合冷榨、热榨菜籽油、花生油、大豆油、茶籽油、牡丹籽油、胡麻油等毛油的澄清过滤，滤后的油脂达到不起沫、少油烟、无沉淀物。可连续加工大量油脂。气压式滤油机是通过空气正压方式滤油，使毛油通过多层高密度滤油布进行精滤，从而实现毛油的油、渣分离。……

§ YY-60型气压滤油机

Air pressure type oil filter for small oil factory users, filtration and clarification of cold pressing and hot pressing for rapeseed oil, peanut oil, soybean oil, tea seed oil, sesame oil, peony seed oil, crude oil, filter out of the oil to foam, less smoke, no sediment. Continuous processing of large amounts of grease. Air pressure type oil filter through the air positive pressure filter oil, crude oil fine filter through the multilayer high density filter cloth, oil, slag in order to separate the crude oil. …

产品规格
Product specifications

产品型号 Product model	工作压力 Working pressure	加工能力 Processing capacity	滤桶直径	整机重量	配用电源 Power Supply	电机功率 Motor power	桶数
（60型）气压滤油机	0.1-0.5Mpa	[illegible]	580×2mm	200KG	380/220V	2.2Kw	双桶

§ 80型离心式滤油机

80型离心式滤油机是我厂自主研发的又一款新型滤油机。本机是利用其形成的高速旋转使毛油中的油、水、杂质受到不同的离心力的作用迅速分离，从而达到高速过滤的效果，过滤后的油质纯度高，色泽清亮、无杂质、不起泡。

80 type centrifugal filter oil machine is my factory independent research and development and a new filter oil machine. This machine is the High-speed rotating makes hair with the left cylinder oil in the oil, water and impurities by different centrifugal force Rapid separation, thus achieve high-speed filtering effect, the filtered oil high purity, Colour and lustre is clear, without impurities, no bubbles.

产品规格
Product specifications

产品型号 Product model	高度 Highly	周长 The perimeter	重量 The weight of the	电压 Power Supply	处理量 processing
（80）型离心式滤油机	1058mm	1800mm	[illegible]	380/220V	400-500kg/h

§ 千层双压式精滤滤油机

[illegible]

§ 碳钢油脂精炼设备（1-100吨均可定做）

精炼工艺流程

本车间采用间歇精炼的生产工艺，根据毛油的种类和品质不同，调整工艺参数，选择不同的精炼方式，可以生产一、二、三、四级油。我们所提供的工艺设备有如下特点：

——灵活方便的调节性，即使原料品质略有变化仍可正常生产；

——全连续化的操作系统；

——最大限度的热量回收，节能效果显著；

——全封闭的操作体系，避免了油脂的氧化，确保产品的高品质与稳定性；

——采用先进的物理精炼工艺，有效的提高了精炼率，同时大大减少污水量，污水处理费用。

——研发设计生产的精炼设备规模日产1-300吨，均可设计制造。工程设计全部借助于CAD设计系统，可为客户提供整体设计和专项设计，为用户提供国内一流的先进技术和油脂精炼脱蜡设备。

The workshop uses gap refining process, according to different types and quality of crude oil, adjust the process parameters, choose different refining methods, you can produce one or two, three, grade oil. The process equipment we provide has the following characteristics:

— flexibility, ease of adjustment, even if the quality of raw materials change slightly, still normal production;

— a fully continuous operating system;

— maximum heat recovery, energy-saving effect is remarkable;

Completely closed operation system, avoid the oxidation of grease, ensure the high quality and stability of products;

Using advanced physical refining process, the refining rate is improved effectively. At the same time greatly reduce the amount of sewage, sewage treatment costs.

—— Research and design of production scale Nissan 1-300 tons of refining equipment, can design and manufacture, engineering design with the help of all CAD design system, can provide the overall design and special design for customers, provide the domestic first-class advanced technology and oil refining and dewaxing apparatus for users.

§ 不锈钢油脂精炼设备（1-100吨均可定做）

§ U型自动熬油锅（30-300吨均可定做）

[illegible]

§ 负压熬油锅（30-300吨均可定做）

[illegible]

产品规格
Product specifications

产品型号 Product model	工作压力 Working pressure	容量 capacity	直径	料筒长度	配用电源 Power Supply	电机功率 Motor power
[illegible]	[illegible]	1-300吨	1500-5000mm（可定做）	3-6m	380V	[illegible]

60预榨机

本机具有生产处理量大，操作简单，占地面积小，能耗低，干饼结构疏松不留毒性点，广泛用于油料作物（大豆、菜籽、花生、胡麻）等。
加工的预榨工艺使用电源"380V，配套功率，11千瓦（可选7.5千瓦）

碎饼机

本机适用于各种豆饼、花生饼、棉籽饼及其它块状、粒状物料，结构简单，维修方便，是广大饲料加工厂的必备产品。
配套功率：7.5-11千瓦，
使用电源：380伏。

370茶籽粉碎机

本机是新型茶籽粉碎机械，具有操作简便、日产量高、无油腻等优点，可广泛应用于茶籽及其他食物的粉碎加工。

配套功率：7.5-15千瓦，
使用电源：380伏。

无压蒸汽锅

本产品是榨油热榨所需配套设备之一，适用于工艺需要加热的油料作物（如大豆、花生、葵籽、茶籽等）。
配套功率：9千瓦，
使用电源：380伏。

全自动导热平底炒锅

80厘米
90厘米
100厘米
120厘米
150厘米

本导热油锅为[illegible]

130 100 型封闭式滚筒炒籽机

使用电源：380V/220V
电机功率：1.5KW
本机是榨油机热榨、使温压榨所需设备之一，适用于颗粒状油料的加热焙炒。本机对油料加热的同时，可快速降低水分，有利于葵花籽、花生、瓜子等炒制食品的加工

液压包饼机

适用对象：菜籽,茶籽,大豆,花生,花椒籽,葵花籽,棉籽,米糠,乌桕籽,油桐籽,油棕果,玉米,芝麻
配用动力：1.5（kw）
处理量：120（kg/h）

本机省时省力，省人工，降低劳动成本。压饼速度快，[illegible]

§ 全自动导热油电炒锅

80厘米
90厘米
100厘米
120厘米
全自动导热平底电炒锅

[illegible]

特点：
恒温控制，节能，环保。
Features:
Constant temperature control,
energy saving, environmental protection

§ 自动上料炒籽机

产品规格
Product specifications

产品型号 Product model	长度	宽度	高度	重量	电压	配用电机	生产量
[illegible]	[illegible]	3000mm	2800mm	[illegible]	380V	[illegible]	[illegible]

§ 冻肉粉碎机

1、通用性好，适用范围广，生产效率高；
2、具有冻肉、冻肉块粉碎功能，省时、省力，保鲜，保质产量5-10吨，加工能力强。
3、粉碎过程周期短，温升低，有利于保鲜，延长质保期。
1. good versatility, wide range of application, high production efficiency;
2. with meat, frozen block grinding function, time-saving and labor-saving, fresh-keeping and quality; yield 5-10 tons, strong processing ability.
3. the grinding process is short, low temperature rise, conducive to preservation, extend the warranty period.

§ 不锈钢滚筒电磁炒锅

该产品采用电磁加热，操作方便，功率分档可调，升温快，温度高，操作安全可靠，节能环保。
主要适用于胡麻、芝麻、瓜子、花生、大豆、菜籽、辣椒籽、中草药、化工原料等
The product adopts electromagnetic heating, easy operation, adjustable power shift, fast heating, high temperature, safe and reliable operation, energy saving and environmental protection.
It is mainly suitable for linseed, sesame, melon seeds, peanuts, soybeans, rapeseed, pepper seeds, Chinese herbal medicine, chemical raw materials, etc.

产品规格
Product specifications

产品型号 Product model	电磁功率	加工能力	桶直径	整机重量	配用电源 Power Supply	电机功率 Motor power
[illegible]	80KW（可定做）	[illegible]（可定做）	[illegible]（可定做）	600KG	380V	4Kw

冷冻脱蜡设备

◎油脂脱蜡设备主要是指去除蜡脂使油品色泽鲜亮。工艺流程：结晶、养晶、蜡脂过滤、冷水循环等来完成的。
Oil dewaxing equipment mainly refers to the removal of wax grease to make the oil color bright. Process flow: crystallization, crystallization, wax filtration, cold water circulation and so on.

配套灌装机系列

全自动直线灌装机

半自动灌装机

◎全机采用技术成熟的PLC控制系统，使整机运行稳定，高速；
◎操作系统采用触摸屏控制，操作简单、实用、效率高；
◎操作简单方便，功能全，能耗低，投资少，自动化程度高。
The whole machine adopts PLC control system technology is mature, the stable operation, high speed;
The operating system uses touch screen control, simple operation, practicability, high efficiency;
The simple and convenient operation, complete function, low energy consumption, low investment, high degree of automation.

技术参数

灌装头数	灌装量	适用瓶高	适用瓶口径	外形尺寸	生产能力	精度	整机功率
12头	50-1000mL	50-400mm	大于12mm	2000*800*2100	[illegible]	≤0.3%	0.55Kw

榨取花生油流程



榨取豆油/[illegible]



榨取茶籽油流程



榨取胡麻油流程



产品使用注意事项

1、为确保用户安全，请不要自行打开油泵盖，修理时应由专业人员进行。
2、使用时，点击电机开关五至十次排除油管内空气。
冬季，让电机空转五至十分钟，让油变稀。
3、本机使用的液压油夏季为32#，冬季为46#液压油，粘度用50℃时60厘泊。（液压油质量越好，液压缸越耐用）
4、保证液压油的清洁，油箱内无杂物。
5、机器放置于平坦位置并远离火种。
6、机器放平后把油箱回油管与榨框下方铁管连接，回油管与油箱回油螺丝连接，安全阀油管放入油箱即可。
7、当油管漏油时，请勿用手去堵，应先及时切断动力，再更换油管。
8、榨油机的液压油正常工作强度下，液压油每年更换一次。

故障现象及排除

1、榨油机无压力，可检查电机是否正传，油泵密封圈是否损坏，油泵吸油管是否堵塞。
2、榨油机压力不稳定，可检查油箱是否有杂质，单向止回阀是否密封不严，油管内是否有空气。（检测办法：当压力升至20Mpa时把与保压阀连接的铁管快速卸开看单向止回阀是否回油，如不回油可能是有无密封圈损坏，或换向阀老化，需要更换配件。如油管内有空气，即开油管排除空气）。

备注

1、在使用我厂产品前，请仔细阅读本说明书。
2、我厂产品不得擅自涂改外观，擅自涂改，自愿放弃保修权。
3、我厂的各项产品均可根据用户要求，设计定做。
4、产品如有调整，恕不另行通知。
5、购机后，我厂会安排专业人员上门安装、指导、包教包会，壹年保修，终身维护。
6、本册提到的相关内容最终解释权归山东盛世赫程机械有限公司所有。

尊敬的用户：

感谢您在百忙之中细阅本公司产品！

在您选择榨油机的时候有没有遇到以下问题：

1.为什么榨油机出油率低？
2.为什么榨油机料筒出渣？
3.为什么榨出的油脂浑浊？
4.为什么同样的产品出油率不一样？

机器有价，技术和经验无价！

我们愿意分享我们的技术和经验给信任我们产品的用户和朋友们。

我公司郑重承诺：

自您购买我司产品之日起，我司将无偿提供给您所有的榨油技术和经验；帮助用户解决在生产中遇到的所有问题。

钱隆牌榨油机愿与您共创美好明天！